



## 8" x 8" x 4" Underwater Muffler Vertical

### Part # 107V800

Underwater exhaust mufflers provide the best sound attenuation and exhaust reduction by discharging below the hull. At idle speeds a small bypass is used to vent to atmosphere to reduce engine backpressure. All underwater exhaust mufflers are provided with a white gel coat finish and are equipped with stainless crush sleeves inside the inlets and outlets. For installations where the engine is above the waterline only.

Underwater Exhaust

### MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass/Resin Ratio	60%

### ATTRIBUTES

A1 - Inlet/Outlet (IN/MM)	8/204
A2 - Bypass (IN/MM)	4/102
B1 - I/O Length (IN/MM)	8/204
B2 - Bypass Length (IN/MM)	4.5/115
C - Length (IN/MM)	31/788
D - Diameter (IN/MM)	18.5/470
E1 - Inlet Elevation (IN/MM)	23.25/591
E2 - Bypass Elevation	3.75/96
H - Height (IN/MM)	31.5/801
Color	White Gel Coat
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

