



2" X 2" Vernalift™ (Side In) 10" X 10"

Part # 1500027

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

| | |
|---------------------|--|
| Process | Filament Winding CNC, Resin Transfer Molding |
| Resin | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass | Corrosion-Resistant E Glass |
| Glass / Resin Ratio | 60% |

ATTRIBUTES

| | |
|----------------------------|--|
| A1 - Inlet (IN / MM) | 2.00 / 51 |
| A2 - Outlet (IN / MM) | 2.00 / 51 |
| B - I/O Length (IN / MM) | 2.50 / 64 |
| D - Diameter (IN / MM) | 10.04 / 255 |
| E - Inlet Height (IN / MM) | 6.50 / 165 |
| F - I/O Offset (IN / MM) | 2.00 / 51 |
| H - Height (IN / MM) | 10.16 / 258 |
| S - Square Base (IN / MM) | 10.50 / 267 |
| Capacity (Gallons) | 1.31 |
| Color | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals | Lloyd's Register Type Approval |
| Flame Retardancy | UL94V-0 |

