



1.63" X 1.63" Vernalift™ (Inline) 8" X 14"

Part # 1500037

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications. In line design offers installation flexibility when limited space is a challenge.

| MATERIALS AND CONSTRUCTION | |
|----------------------------|--|
| Process | Filament Winding CNC, Resin Transfer Molding |
| Resin | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass | Corrosion-Resistant E Glass |
| Glass / Resin Ratio | 60% |
| ATTRIBUTES | |
| A1 - Inlet (IN / MM) | 1.63 / 41 |
| A2 - Outlet (IN / MM) | 1.63 / 41 |
| B - I/O Length (IN / MM) | 2.00 / 51 |
| C - Length (IN / MM) | 14.00 / 356 |
| D - Diameter (IN / MM) | 8.36 / 212 |
| F - I/O Offset (IN / MM) | 6.18 / 157 |
| Capacity (Gallons) | 1.32 |
| Color | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals | Lloyd's Register Type Approval |
| Flame Retardancy | UL94V-0 |







