



2.88" X 2.88" Vernalift™ (Side Angle In) 10" X 10"

Part # 1500111

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	2.88 / 73
A2 - Outlet (IN / MM)	2.88 / 73
B - I/O Length (IN / MM)	2.50 / 64
D - Diameter (IN / MM)	10.04 / 255
E - Inlet Height (IN / MM)	5.30 / 135
F - I/O Offset (IN / MM)	2.50 / 64
H - Height (IN / MM)	10.16 / 258
N - Angle	45°
S - Square Base (IN / MM)	10.50 / 309
Capacity (Gallons)	1.31
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

