

## Part # 1500155

The Vernalift<sup>™</sup> is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications. In line design offers installation flexibility when limited space is a challenge.

| Vernalift <sup>™</sup> FAMILY | MATERIALS AND            | CONSTRUCTION   |
|-------------------------------|--------------------------|--|
|                               | Process                  | Filament Winding CNC, Resin Transfer Molding                                 |
|                               | Resin                    | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset                           |
|                               | Glass                    | Corrosion-Resistant E Glass  |
|                               | Glass / Resin Ratio      | 60%  |
|                               | ATTRIBUTES               |  |
|                               | A1 - Inlet (IN / MM)     | 1.63 / 41  |
|                               | A2 - Outlet (IN / MM)    | 1.63 / 41  |
|                               | B - I/O Length (IN / MM) | 2.00 / 51  |
|                               | C - Length (IN / MM)     | 17.00 / 432  |
|                               | D - Diameter (IN / MM)   | 10.04 / 255  |
|                               | F - I/O Offset (IN / MM) | 7.52 / 191   |
|                               | Capacity (Gallons)       | 2.29   |
|                               | Color                    | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
|                               | Approvals                | Lloyd's Register Type Approval   |
|                               | Flame Retardancy         | UL94V-0  |







