



3" X 4" Vernalift™ (Side In) 12" X 12"

Part # 1500182

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	3.00 / 76
A2 - Outlet (IN / MM)	4.00 / 102
B - I/O Length (IN / MM)	I - 3.00 / 76 : O - 4.00 / 102
D - Diameter (IN / MM)	12.34 / 313
E - Inlet Height (IN / MM)	7.75 / 197
F - I/O Offset (IN / MM)	2.75 / 70
H - Height (IN / MM)	12.00 / 305
S - Square Base (IN / MM)	13.00 / 330
Capacity (Gallons)	2.47
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

