



## 2" X 2.5" Vernalift™ (Top In) 10" X 10"

### Part # 1500192

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

### MATERIALS AND CONSTRUCTION

|                     |  |
|---------------------|--|
| Process             | Filament Winding CNC, Resin Transfer Molding       |
| Resin               | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass               | Corrosion-Resistant E Glass                        |
| Glass / Resin Ratio | 60%  |

### ATTRIBUTES

|                           |  |
|---------------------------|--|
| A1 - Inlet (IN / MM)      | 2.00 / 51  |
| A2 - Outlet (IN / MM)     | 2.50 / 64  |
| B - I/O Length (IN / MM)  | 2.50 / 64  |
| D - Diameter (IN / MM)    | 10.04 / 255  |
| F - I/O Offset (IN / MM)  | 2.50 / 64  |
| H - Height (IN / MM)      | 10.16 / 258  |
| S - Square Base (IN / MM) | 10.50 / 267  |
| Capacity (Gallons)        | 1.31   |
| Color                     | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals                 | Lloyd's Register Type Approval   |
| Flame Retardancy          | UL94V-0  |

