



5" X 6" Vernalift™ (Side Angle In) 16" X 14.5"

Part # 1500228

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	5.00 / 127
A2 - Outlet (IN / MM)	6.00 / 152
B - I/O Length (IN / MM)	I - 6.00 / 152 : O - 5.00 / 127
D - Diameter (IN / MM)	16.17 / 411
E - Inlet Height (IN / MM)	8.75 / 222
F - I/O Offset (IN / MM)	4.00 / 102
H - Height (IN / MM)	14.50 / 368
N - Angle	45°
S - Square Base (IN / MM)	17.00 / 432
Capacity (Gallons)	5.44
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

