



2" X 1.5" Vernalift™ (Side In) 6" X 9"

Part # 1500292

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	2.00 / 51
A2 - Outlet (IN / MM)	1.50 / 38
B - I/O Length (IN / MM)	2.50 / 64
D - Diameter (IN / MM)	6.38 / 162
E - Inlet Height (IN / MM)	6.00 / 152
F - I/O Offset (IN / MM)	1.50 / 38
H - Height (IN / MM)	9.00 / 229
S - Square Base (IN / MM)	7.00 / 179
Capacity (Gallons)	0.43
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

