



2" X 2" Vernalift™ Dual Stage 8" X 11.25"

Part # 1520200

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A - I/O (IN / MM)	2.00 / 51
B - I/O Length (IN / MM)	2.50 / 64
D - Diameter (IN / MM)	8.38 / 213
E1 - Inlet Height (IN / MM)	4.00 / 102
E2 - Outlet Height (IN / MM)	8.00 / 203
H - Height (IN / MM)	11.25 / 286
S - Square Base (IN / MM)	9.00 / 229
Capacity (Gallons)	0.87
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

