



2.5" X 2.5" Vernalift™ Dual Stage 8" X 12.5"

Part # 1520250

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

| | |
|---------------------|----------------------------------------------------|
| Process | Filament Winding CNC, Resin Transfer Molding |
| Resin | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass | Corrosion-Resistant E Glass |
| Glass / Resin Ratio | 60% |

ATTRIBUTES

| | |
|------------------------------|------------------------------------------------------------------------------|
| A - I/O (IN / MM) | 2.50 / 64 |
| B - I/O Length (IN / MM) | 2.50 / 64 |
| D - Diameter (IN / MM) | 8.38 / 213 |
| E1 - Inlet Height (IN / MM) | 4.25 / 108 |
| E2 - Outlet Height (IN / MM) | 9.00 / 229 |
| H - Height (IN / MM) | 12.50 / 318 |
| S - Square Base (IN / MM) | 9.00 / 229 |
| Capacity (Gallons) | 0.95 |
| Color | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals | Lloyd's Register Type Approval |
| Flame Retardancy | UL94V-0 |

