


Part # 1520500

The Vernalift[™] Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications

	MATERIALS AND CONSTRUCTION	
Vernalift [™] FAMILY	Process	Filament Winding CNC, Resin Transfer Molding
	Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
	Glass	Corrosion-Resistant E Glass
	Glass / Resin Ratio	60%
	ATTRIBUTES	
	A - I/O (IN / MM)	5.00 / 127
	B - I/O Length (IN / MM)	5.00 / 127
	D - Diameter (IN / MM)	12.38 / 314
	E1 - Inlet Height (IN / MM)	5.75 / 146
	E2 - Outlet Height (IN / MM)	13.75 / 349
	H - Height (IN / MM)	19.00 / 483
	S - Square Base (IN / MM)	13.00 / 330
	Capacity (Gallons)	3.74
	Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
	Approvals	Lloyd's Register Type Approval
	Flame Retardancy	UL94V-0







TYPE APPROVA

Centek Marine • 116 Plantation Oak Drive, Thomasville, GA 31792 • 229.228.7653 www.centekmarine.com