



## 6" X 6" Vernalift™ Dual Stage 16" X 22.5"

### Part # 1520600

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications

Vernalift™ FAMILY

### MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

### ATTRIBUTES

A - I/O (IN / MM)	6.00 / 152
B - I/O Length (IN / MM)	6.00 / Part # 152
D - Diameter (IN / MM)	16.25 / 413
E1 - Inlet Height (IN / MM)	7.00 / 178
E2 - Outlet Height (IN / MM)	16.25 / 413
H - Height (IN / MM)	22.50 / 572
S - Square Base (IN / MM)	17.00 / 432
Capacity (Gallons)	8.15
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

