



12" X 12" Vernalift™ Dual Stage 24" X 41"

Part # 1521200

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A - I/O (IN / MM)	12.00 / 305
B - I/O Length (IN / MM)	10.00 / 254
D - Diameter (IN / MM)	24.63 / 626
E1 - Inlet Height (IN / MM)	13.00 / 330
E2 - Outlet Height (IN / MM)	30.00 / 762
H - Height (IN / MM)	41.00 / 1,042
S - Square Base (IN / MM)	26.00 / 660
Capacity (Gallons)	35.6
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

