



8" X 8" Vernalift™ Dual Stage 18" X 29.25" Top Out

Part # 1529004

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

| | |
|---------------------|--|
| Process | Filament Winding CNC, Resin Transfer Molding |
| Resin | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass | Corrosion-Resistant E Glass |
| Glass / Resin Ratio | 60% |

ATTRIBUTES

| | |
|------------------------------|--|
| A - I/O (IN / MM) | 8.00 / 203 |
| B - I/O Length (IN / MM) | 8.00 / 203 |
| D - Diameter (IN / MM) | 18.50 / 470 |
| E1 - Inlet Height (IN / MM) | 9.00 / 229 |
| E2 - Outlet Height (IN / MM) | N/A - Top Outlet |
| H - Height (IN / MM) | 29.25 / 743 |
| S - Square Base (IN / MM) | 19.50 / 495 |
| Capacity (Gallons) | 13.32 |
| Color | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals | Lloyd's Register Type Approval |
| Flame Retardancy | UL94V-0 |

