



BILGEKLEEN™

FOR THE REMOVAL OF OIL AND GAS FROM BILGE WATER

FILTERS BILGE WATER
DISCHARGE

REMOVES HYDROCARBONS

NO INCREASE IN PRESSURE
TO BILGE PUMP

AVAILABLE IN A VARIETY OF
SIZES



The patented BilgeKleen System automatically removes oil, gas, diesel fuel and other hydrocarbon pollutants from bilge water before it is discharged overboard. Using a special filter medium, the BilgeKleen captures and binds to hydrocarbons and lets water pass through freely. As a result, 99.9% of the hydrocarbon pollutants are eliminated from discharge with no increase in pressure to the bilge pump.

SPECIFICATIONS	MINI BILGEKLEEN	BILGEKLEEN - 1	BILGEKLEEN - 2	BILGEKLEEN - 3
PART NUMBER	8-MBK-1	8-BK-1	8-BK-2	8-BK-3
FILTER CAPACITY	MIN 150 GRAMS	MIN 300 GRAMS	MIN 900 GRAMS	MIN 1800 GRAMS
MAXIMUM FLOW	10 GPM	25 GPM	40 GPM	50 GPM
DIMENSIONS IN / OUT	4.5" DIA x 7.5"H 1/2" NPT	4.5" DIA x 12.5"H 1/2" NPT	7.5" DIA x 14"H 1 1/2" NPT	7.5" DIA x 20"H 1 1/2" NPT
REPLACEMENT FILTER	8-M5-1	8-BF-1-1R	8-BF-2-1R	8-BF-3-1R