

## 2.25" x 2.38" Vernalift™ (Side In) 12" X 12"



### Part # 1500080

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

#### Vernalift™ FAMILY

### MATERIALS AND CONSTRUCTION

|                     |  |
|---------------------|--|
| Process             | Filament Winding CNC, Resin Transfer Molding       |
| Resin               | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass               | Corrosion-Resistant E Glass                        |
| Glass / Resin Ratio | 60%  |

### ATTRIBUTES

|                            |  |
|----------------------------|--|
| A1 - Inlet (IN / MM)       | 2.25 / 57  |
| A2 - Outlet (IN / MM)      | 2.38 / 60  |
| B - I/O Length (IN / MM)   | 2.50 / 64  |
| D - Diameter (IN / MM)     | 12.34 / 313  |
| E - Inlet Height (IN / MM) | 8.34 / 212   |
| F - I/O Offset (IN / MM)   | 2.50 / 64  |
| H - Height (IN / MM)       | 12.00 / 305  |
| S - Square Base (IN / MM)  | 13.00 / 330  |
| Capacity (Gallons)         | 2.47   |
| Color                      | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals                  | Lloyd's Register Type Approval   |
| Flame Retardancy           | UL94V-0  |

