

1.5" X 2" Vernalift™ (Side In) 8" X 8"



Part # 1500142

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	1.50 / 38
A2 - Outlet (IN / MM)	2.00 / 51
B - I/O Length (IN / MM)	2.50 / 64
D - Diameter (IN / MM)	8.36 / 212
E - Inlet Height (IN / MM)	4.68 / 119
F - I/O Offset (IN / MM)	2.00 / 51
H - Height (IN / MM)	8.00 / 203
S - Square Base (IN / MM)	9.00 / 229
Capacity (Gallons)	0.78
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

