4” X 5” Vernalift™ (Side In) 16” X 16”

CENTEK MARINE

Part # 1500149

The Vernalift™ is the industry’s best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION	
Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%
ATTRIBUTES	
A1 - Inlet (IN / MM)	4.00 / 102
A2 - Outlet (IN / MM)	5.00 / 127
B - I/O Length (IN / MM)	5.00 / 127
D - Diameter (IN / MM)	16.17 / 411
E - Inlet Height (IN / MM)	8.75 / 222
F - I/O Offset (IN / MM)	4.00 / 102
H - Height (IN / MM)	16.00 / 406
S - Square Base (IN / MM)	17.00 / 432
Capacity (Gallons)	6.05
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd’s Register Type Approval
Flame Retardancy	UL94V-0





Lloyd’s Register TYPE APPROVAL

ISO 9001:2015

Centek Marine • 116 Plantation Oak Drive, Thomasville, GA 31792 • 229.228.7653
www.centekmarine.com