

8" X 10" Vernalift™ (Side Angle In) 24" X 24"



Part # 1500251

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	8.00 / 203
A2 - Outlet (IN / MM)	10.00 / 254
B - I/O Length (IN / MM)	8.00 / 203
D - Diameter (IN / MM)	24.60 / 625
E - Inlet Height (IN / MM)	12.00 / 305
F - I/O Offset (IN / MM)	6.00 / 152
H - Height (IN / MM)	24.00 / 610
N - Angle	45°
S - Square Base (IN / MM)	26.00 / 660
Capacity (Gallons)	21.76
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

