

# 6" X 8" Vernalift™ (Side Angle In) 18" X 18"



## Part # 1500282

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

### MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

### ATTRIBUTES

A1 - Inlet (IN / MM)	6.00 / 152
A2 - Outlet (IN / MM)	8.00 / 203
B - I/O Length (IN / MM)	6.00 / 152
D - Diameter (IN / MM)	18.50 / 470
E - Inlet Height (IN / MM)	9.31 / 237
F - I/O Offset (IN / MM)	3.00 / 76
H - Height (IN / MM)	18.00 / 457
N - Angle	45°
S - Square Base (IN / MM)	19.00 / 483
Capacity (Gallons)	8.8
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

