

3.5" X 5" Vernalift™ (Inline) 12" X 22"



Part # 1500300

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications. In line design offers installation flexibility when limited space is a challenge.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A1 - Inlet (IN / MM)	3.50 / 89
A2 - Outlet (IN / MM)	5.00 / 127
B - I/O Length (IN / MM)	I - 4.00 / 102 : O - 5.00 / 127
C - Length (IN / MM)	22.00 / 559
D - Diameter (IN / MM)	12.34 / 313
F - I/O Offset (IN / MM)	I - 3.75 / 95 : O - 3.00 / 76
Capacity (Gallons)	4.83
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

