2.38" X 2.38" Vernalift™ (Top In) 12" X 12"



Part # 1500303

The Vernalift™ is the industry's best lift muffler and meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

| MATERIALS AND CONSTRUCTION | |
|----------------------------|--|
| Process | Filament Winding CNC, Resin Transfer Molding |
| Resin | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass | Corrosion-Resistant E Glass |
| Glass / Resin Ratio | 60% |
| ATTRIBUTES | |
| A1 - Inlet (IN / MM) | 2.38 / 60 |
| A2 - Outlet (IN / MM) | 2.38 / 60 |
| B - I/O Length (IN / MM) | 3.00 / 76 |
| D - Diameter (IN / MM) | 12.34 / 313 |
| F - I/O Offset (IN / MM) | 2.75 / 70 |
| H - Height (IN / MM) | 12.00 / 305 |
| S - Square Base (IN / MM) | 13.00 / 330 |
| Capacity (Gallons) | 2.47 |
| Color | Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals | Lloyd's Register Type Approval |
| Flame Retardancy | UL94V-0 |









