

3.5" X 3.5" Vernalift™ Dual Stage 10" X 15.25"



Part # 1520350

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

ATTRIBUTES

A - I/O (IN / MM)	3.50 / 89
B - I/O Length (IN / MM)	3.50 / 89
D - Diameter (IN / MM)	10.06 / 256
E1 - Inlet Height (IN / MM)	5.25 / 133
E2 - Outlet Height (IN / MM)	11.00 / 280
H - Height (IN / MM)	Part # 15.25 / 387
S - Square Base (IN / MM)	10.50 / 267
Capacity (Gallons)	1.78
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

