

# 5" X 5" Vernalift™ Dual Stage 12" X 19"



## Part # 1520500

The Vernalift™ Dual Stage is the industry's best lift muffler and offers excellent sound attenuation. Meets or exceeds the requirements of the ABYC P-1 Standards. Use with propulsion engines or generators located above or below water line. For gas or diesel applications.

Vernalift™ FAMILY

### MATERIALS AND CONSTRUCTION

Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass / Resin Ratio	60%

### ATTRIBUTES

A - I/O (IN / MM)	5.00 / 127
B - I/O Length (IN / MM)	5.00 / 127
D - Diameter (IN / MM)	12.38 / 314
E1 - Inlet Height (IN / MM)	5.75 / 146
E2 - Outlet Height (IN / MM)	13.75 / 349
H - Height (IN / MM)	19.00 / 483
S - Square Base (IN / MM)	13.00 / 330
Capacity (Gallons)	3.74
Color	Standard Black; White, Gel-Coat, Yacht Quality, Yacht Quality Plus Available
Approvals	Lloyd's Register Type Approval
Flame Retardancy	UL94V-0

