

# 5" X 5" X 3" Combo-Sep Horizontal



## Part # 104H500

Centek Combo-Septs™ combine the sound attenuation features of a muffler with a gas/water separation system to divert the exhaust gas and cooling water to separate outboard ports. The inlets and outlets are available in other configurations. Contact Centek Engineering Department for more details.

Combo-Sep™ Horizontal

### MATERIALS AND CONSTRUCTION

|                   |                                                    |
|-------------------|----------------------------------------------------|
| Process           | Filament Winding CNC, Resin Transfer Molding       |
| Resin             | Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset |
| Glass             | Corrosion-Resistant E Glass                        |
| Glass/Resin Ratio | 60%                                                |

### ATTRIBUTES

|                         |                                                                              |
|-------------------------|------------------------------------------------------------------------------|
| A1-Inlet (IN/MM)        | 5.00/127                                                                     |
| A2-Gas Outlet (IN/MM)   | 5.00/127                                                                     |
| A3-Drain (IN/MM)        | 3.00/76                                                                      |
| B-I/O Length (IN/MM)    | 5.00/127                                                                     |
| C-Length (IN/MM)        | 65.00/1651                                                                   |
| F-Outlet Offset (IN/MM) | 3.00/76                                                                      |
| H-Height (IN/MM)        | 19.00/483                                                                    |
| I-Width (IN/MM)         | 12.00/305                                                                    |
| M-Drain Offset (IN/MM)  | 4.00/102                                                                     |
| Color                   | Standard White; Black, Gel-Coat, Yacht Quality, Yacht Quality Plus Available |
| Approvals               | Lloyd's Register Type Approval                                               |
| Flame Retardancy        | UL94V-0                                                                      |

