6” X 6” X 3” Underwater Muffler Vertical

CENTEK MARINE

Part # 107V600

Underwater exhaust mufflers provide the best sound attenuation and exhaust reduction by discharging below the hull. At idle speeds a small bypass is used to vent to atmosphere to reduce engine backpressure. All underwater exhaust mufflers are provided with a white gel coat finish and are equipped with stainless crush sleeves inside the inlets and outlets. For installations where the engine is above the waterline only.

Underwater Exhaust

MATERIALS AND CONSTRUCTION	
Process	Filament Winding CNC, Resin Transfer Molding
Resin	Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset
Glass	Corrosion-Resistant E Glass
Glass/Resin Ratio	60%
ATTRIBUTES	
A1 - Inlet/Outlet (IN/MM)	6/153
A2 - Bypass (IN/MM)	3/76
B1 - I/O Length (IN/MM)	6/153
B2 - Bypass Length (IN/MM)	4/102
C - Length (IN/MM)	24/610
D - Diameter (IN/MM)	14.5/369
E1 - Inlet Elevation (IN/MM)	18/458
E2 - Bypass Elevation	13/330
H - Height (IN/MM)	24.5/623
Color	White Gel Coat
Approvals	Lloyd’s Register Type Approval
Flame Retardancy	UL94V-0



Lloyd’s Register TYPE APPROVAL

ANAB ACCREDITED ISO 9001:2015

Centek Marine • 116 Plantation Oak Drive, Thomasville, GA 31792 • 229.228.7653
www.centekmarine.com